

"HALF PIPE LOG IN TROUGH" CONFIGURATION – DIMENSIONS

INCH DIMENSIONS IN SHADED AREA

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
685	482.6	129.8	304.8	292.1	1727	584.2	311.2	31.4	12.7	9.5	19.1	304.8	330.2	947.6
26.97	19.00	5.11	12.00	11.50	68	23.00	12.25	1.23	0.50	0.38	0.75	12.00	13.00	37.31
785	584.2	129.0	355.6	342.9	1930	685.8	362.0	30.6	12.7	9.5	19.1	457.2	482.6	1107.2
30.91	23.00	5.08	14.00	13.50	76	27.00	14.25	1.20	0.50	0.38	0.75	18.00	19.00	43.59
885	685.8	128.2	406.4	393.7	2134	787.4	412.8	29.8	12.7	9.5	19.1	609.6	635.0	1266.8
34.84	27.00	5.05	16.00	15.50	84	31.00	16.25	1.17	0.50	0.38	0.75	24.00	25.00	49.87
985	787.4	127.4	431.8	444.5	2337	889.0	463.6	29.0	12.7	9.5	19.1	609.6	635.0	1426.4
38.78	31.00	5.01	17.00	17.50	92	35.00	18.25	1.14	0.50	0.38	0.75	24.00	25.00	56.16
1085	889.0	126.6	482.6	495.3	2540	990.6	514.4	28.2	12.7	9.5	19.1	762.0	787.4	1586.0
42.72	35.00	4.98	19.00	19.50	100	39.00	20.25	1.11	0.50	0.38	0.75	30.00	31.00	62.44
1185	990.6	125.8	533.4	546.1	2743	1092.2	565.2	27.4	12.7	9.5	19.1	762.0	787.4	1745.5
46.65	39.00	4.95	21.00	21.50	108	43.00	22.25	1.08	0.50	0.38	0.75	30.00	31.00	68.72
1285	1041.4	163.1	584.2	584.2	2946	1168.4	603.3	39.3	12.7	9.5	19.1	914.4	939.8	1865.2
50.59	41.00	6.42	23.00	23.00	116	46.00	23.75	1.55	0.50	0.38	0.75	36.00	37.00	73.43
1385	1143.0	162.3	635.0	635.0	3150	1270.0	654.1	38.5	12.7	9.5	19.1	914.4	939.8	2024.8
54.53	45.00	6.39	25.00	25.00	124	50.00	25.75	1.51	0.50	0.38	0.75	36.00	37.00	79.72
1485	1244.6	148.8	660.4	673.1	3353	1346.2	692.2	50.4	12.7	9.5	19.1	1066.8	1092.2	2144.5
58.46	49.00	5.86	26.00	26.50	132	53.00	27.25	1.98	0.50	0.38	0.75	42.00	43.00	84.43
1585	1371.6	122.6	711.2	723.9	3505	1447.8	743.0	49.6	12.7	9.5	19.1	1066.8	1092.2	2304.1
62.40	54.00	4.83	28.00	28.50	138	57.00	29.25	1.95	0.50	0.38	0.75	42.00	43.00	90.71
1685	1447.8	134.5	762.0	762.0	3708	1524.0	781.1	61.5	12.7	9.5	19.1	1219.2	1244.6	2423.8
66.34	57.00	5.29	30.00	30.00	146	60.00	30.75	2.42	0.50	0.38	0.75	48.00	49.00	95.43
1785	1574.8	108.3	812.8	812.8	3912	1625.6	831.9	60.7	12.7	9.5	19.1	1219.2	1244.6	2583.4
70.28	62.00	4.26	32.00	32.00	154	64.00	32.75	2.39	0.50	0.38	0.75	48.00	49.00	101.71
1885	1676.4	107.5	863.6	863.6	4115	1727.2	882.7	59.9	12.7	9.5	19.1	1320.8	1346.2	2743.0
74.21	66.00	4.23	34.00	34.00	162	68.00	34.75	2.36	0.50	0.38	0.75	52.00	53.00	107.99
1985	1778.0	94.0	914.4	901.7	4318	1803.4	920.8	71.8	12.7	9.5	19.1	1524.0	1549.4	2862.7
78.15	70.00	3.70	36.00	35.50	170	71.00	36.25	2.82	0.50	0.38	0.75	60.00	61.00	112.70



DATE: OCT 2006	METAL DETECTOR SEARCH COIL TROUGH
REVISION: 1	DWG: TTSI- 2012A